

# TWO-TIER

## STANDARD SPECIFICATIONS

### DIFFUSER

The two tier drum is a modern take on the traditional style. The UV stabilized white acrylic with fabric material bonded to the exterior.

### HOUSING

Formed, cold rolled steel design, finished in a high reflectance powder coat white.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs

Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

24/30 Size: R34 - 34W nominal, .28 A input - 3792 lm. Dimmable (0-10V).

24/30 Size: R49 - 49W nominal, .41 A input - 5039 lm. Dimmable (0-10V).

### MOUNTING

Directly to j-box (by others). Mounting hardware included.

### SUSPENSION SYSTEM

The 2604 Series is available in multiple colors and four suspension methods:

**CC1 - Cord & Single Cable:** Both the power cord and aircraft cable can be trimmed in the field. See optional ordering code CE1 and CE2 for extended 10' and 20' drops.

**CC3 - Cord & Three Cable:** Both the power cord and aircraft cables can be trimmed in the field. See optional ordering code CE1 and CE2 for extended 10' and 20' drops.

**SCM - Stem & Cable Mount:** Steel stem in your choice of finish with three aircraft cables. The standard overall height (OAH) can be extended with additional stem sections in 1' and 2' intervals - see accessories section.

**SSM - Single Stem Mount:** Traditional pendant style. Steel stem in your choice of finish. The standard overall height (OAH) can be extended with additional stem sections in 1' and 2' intervals - see accessories section.

### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

## ORDERING INFORMATION

2604							
Model	2.	3.	4.	5.	6.	7.	8. (if required)
	<b>2. SIZE</b>		<b>4. WATTAGE</b>	<b>5. DIFFUSER</b>		<b>7. COLOR TEMPERATURE</b>	<b>8. AVAILABLE OPTIONS</b>
	24 24" dia. 30 30" dia.		R34 34W R Series LED R49 49W R Series LED	NAL Natural Linen WHL White Linen		35K 3500K standard color temperature 27K 2700K color temperature 30K 3000K color temperature 40K 4000K color temperature	90R <sup>0</sup> 90 CRI (30K & 35K only) BAC <sup>1</sup> Buy American Compliant CE1 3' - 10' Cord/Cable Extension (CC1 & CC3 only) CE2 10' - 20' Cord/Cable Extension (CC1 & CC3 only) DTR <sup>4</sup> Triac (Line Voltage) Dimming (120V) ES <sup>6</sup> ENERGY STAR <sup>®</sup> (Not available in 90 CRI) FCL <sup>7</sup> French Canadian Labels T24 <sup>9</sup> Title 24 JA8 Compliant (30K & 35K only)
	<b>3. FINISH</b>			<b>6. SUSPENSION</b>			
	CC1 & CC3 BL Black NT Nickel Tone WH White  SCM & SSM BL Black BZ Bronze GM Gun Metal MB Metallic Bronze MG Metallic Gold NT Nickel Tone PL Platinum WH White			CC1 Cord & Single Cable CC3 Cord & Three Cable SCM Stem & Cable Mount SSM Single Stem Mount			
	<b>ACCESSORIES</b> (field installed - order separately)						
	390001xx SCM Extension Kit: includes (1) 1' stem and (2) 2' stems. 5' combined max. Specify finish (xx)						
	390002xx SSM Extension Kit: includes (1) 1' stem and (2) 2' stems. 5' combined max. Specify finish (xx)						
	320029WHA Top Cover Set: 24 size, White Acrylic						
	320030WHA Top Cover Set: 30 size, White Acrylic						

**Universal Footnotes (only applies if option is listed on spec sheet):** (0) 90R - 90 CRI output-loss multiplier: 0.85 (estimate). Cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW or EXT. (3) BLD - includes integral microwave motion sensor (do not combine with OCC option). Cannot be combined with DTR. (4) DTR - cannot be combined with BLD. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC. (8) OCC - integral microwave motion sensor (ON/OFF). (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with ES. (10) PCH/PC4 - cannot be combined with BLD or OCC. **Add'l Notes:** \*BBI/BBC - BBI minimum operating temp: 10C/50F unless otherwise stated. BBC minimum operating temp: -20C/-4F. \*\*BLD - integral microwave motion sensor with step-dim control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to set level. 3: Remain in continuous dimmed state or turn off after set period. Configurable via onboard dip switches.


**Specifications and dimensions subject to change without notice.**

Consult your Brownlee Lighting representative for availability and ordering information.


<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>




WH finish, WHL diffuser, CC3 suspension




SSM suspension



SCM suspension



CC1 suspension



CC3 suspension

