

# REFLEX

## STANDARD SPECIFICATIONS

### FRAME

Cold rolled steel, roll formed and assembled with rivets. The assembly has multiple stiffening edges for durability.

### DIFFUSER

Translucent, UV stabilized white acrylic. The material is flex ible to withstand minor impact without breaking.

### PAN

Formed, cold rolled steel design, finished with a powder coat high reflectance white paint.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs

Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B06 - 6W nominal, .05 A input - 571 lm. Non-dimming.

B12 - 12W nominal, .10 A input - 1130 lm. Dimmable (0-10V).

C09 - 9W nominal, .10 A input - 797 lm. Dimmable (0-10V).

C17 - 16W nominal, .15 A input - 1633 lm. Dimmable (0-10V).

C24 - 23W nominal, .20 A input - 2240 lm. Dimmable (0-10V).

### MOUNTING

Directly to j-box (by others). Mounting hardware included.

### FINISH

The 1380 series is available in all Brownlee paint finishes as a standard offering.

### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

## ORDERING INFORMATION

**1380** - \_\_\_\_\_  
 Model                      2.                      3.                      4.                      5.

### 2. FINISH

#### STANDARD

<b>AB</b>	Antique Bronze
<b>AS</b>	Antique Silver
<b>BL</b>	Black
<b>BZ</b>	Bronze
<b>DB</b>	Desert Bronze
<b>GM</b>	Gun Metal
<b>MB</b>	Metallic Bronze
<b>MG</b>	Metallic Gold
<b>NT</b>	Nickel Tone
<b>PL</b>	Platinum
<b>WH</b>	White

#### CUSTOM

Provide color sample or RAL code to match

### 3. WATTAGE

<b>B06</b>	6W B Series LED
<b>B12</b>	12W B Series LED
<b>C09</b>	9W C Series LED
<b>C17</b>	16W C Series LED
<b>C24</b>	23W C Series LED



### 4. COLOR TEMPERATURE

<b>35K</b>	3500K standard color temperature
<b>27K</b>	2700K color temperature
<b>30K</b>	3000K color temperature
<b>40K</b>	4000K color temperature

### 5. AVAILABLE OPTIONS

<b>90R<sup>0</sup></b>	90 CRI (3000K only)
<b>BAC<sup>1</sup></b>	Buy American Compliant
<b>BLD<sup>3**</sup></b>	Bi-Level Dimming (All except B06)
<b>DTR<sup>4</sup></b>	Triac (Line Voltage) Dimming (120V) (All except B06)
<b>ES<sup>6</sup></b>	ENERGY STAR® (Not available in 90 CRI)
<b>FCL<sup>7</sup></b>	French Canadian Labels
<b>OCC<sup>8</sup></b>	Occupancy Sensor
<b>T24<sup>9</sup></b>	Title 24 JA8 Compliant (B12 & C24 in 3000K only)
<b>TBC</b>	Top/Bottom Covers (Perforated)

<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>



**Notes:** (0) **90R** - cannot be combined with ES. (1) **BAC** - cannot be combined with FCL. (2) **BBI/BBS/BBC** - cannot be combined with ECW, EXT, or T24. (3) **BLD** - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) **DTR** - cannot be combined with BLD or T24. (5) **ECW** - cannot be combined with BBI, BBC, or DTR. (6) **ES** - cannot be combined with 90R or T24. (7) **FCL** - cannot be combined with BAC or T24. (8) **OCC** - integral ON/OFF occupancy sensor. (9) **T24** - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI, BBC, BBS, BLD, DTR, ES, or FCL. (10) **BBS** - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) **PCH/PC4** - cannot be combined with BLD or OCC. **Add'l Notes:** \***BBI/BBS/BBC** - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\***BLD** - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

### Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.