

# STANDARD SPECIFICATIONS

Cold rolled steel, roll formed and assembled with rivets. The assembly has multiple stiffening edges for durability.

### **DIFFUSER**

Translucent, UV stabilized white acrylic. The material is flexible to withstand minor impact without breaking.

#### PAN

Formed aluminum design, finished with a powder coat high reflectance white paint.

# **LED PERFORMANCE - 3500K STANDARD**

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs Amperage rated @ 110V input

Operating ambient temperature:  $-20^{\circ}\text{C}\,/\,-4^{\circ}\text{F}\,-\,40^{\circ}\text{C}\,/\,104^{\circ}\text{F}$ 

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B06 - 6W nominal, .05 A input - 545 lm. Non-dimming.

B12 - 12W nominal, .10 A input - 1078 lm. Dimmable (0-10V).

C09 - 9W nominal, .10 A input - 760 lm. Dimmable (0-10V).

C17 - 16W nominal, .15 A input - 1557 lm. Dimmable (0-10V).

C24 - 23W nominal, .20 A input - 2137 lm. Dimmable (0-10V).

## **MOUNTING**

Directly to j-box (by others). Mounting hardware included.

PΙ

WH

Platinum

White

**CUSTOM** Provide color sample or RAL

code to match


The 1392 series is available in all Brownlee paint finishes as a standard offering.

## WARRANTY

5 year limited warranty on this LED product. Consult factory for details.









**BZ** finish







# ORDERING INFORMATION

1392	-		-		-		-	
Model		2.		3.		4.		5. (if required)

WATTAGE

AB AS	STANDARD Antique Bronze Antique Silver	B06 B12	6W B Series LED 12W B Series LED	3
BL BZ DB GM MB MG NT	Black Bronze Desert Bronze Gun Metal Metallic Bronze Metallic Gold Nickel Tone	C09 C17 C24	9W C Series LED 16W C Series LED 23W C Series LED	4

35K 27K 30K 40K	3500K standard color temperature 2700K color temperature 3000K color temperature 4000K color temperature	90R <sup>0</sup> BAC <sup>1</sup> BBI <sup>2*</sup>	90 Bu Int Bate with
		BLD <sup>3**</sup> DTR <sup>4</sup>	Bi- Tri (All
		ES <sup>6</sup> FCL <sup>7</sup>	EN Fre

**COLOR TEMPERATURE** 

5. A\	AILABLE OPTIONS
90R <sup>0</sup>	90 CRI (3000K only)
BAC <sup>1</sup>	Buy American Compliant
BBI <sup>2*</sup>	Integral Battery Backup (8W) Battery must be connected to continuous power supply within 7 Mo. of shipping. See Warranty Note 3.
BLD <sup>3**</sup>	Bi-Level Dimming (B12 only)
DTR <sup>4</sup>	Triac (Line Voltage) Dimming (120V) (All except B06)
ES <sup>6</sup>	ENERGY STAR® (Not available in 90 CRI)
FCL <sup>7</sup>	French Canadian Labels
OCC8	Occupancy Sensor (B12 only)
T24 <sup>9</sup>	Title 24 JA8 Compliant (B12 & C24 in 3000K only)
TBC	Top/Bottom Covers (Perforated)

Universal Footnotes (only applies if option is listed on spec sheet): (0) 90R - 90 CRI output-loss multiplier: 0.85 (estimate). Cannot be combined with ES. 1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW or EXT. (3) BLD - includes integral microwave motion sensor (do not combine with OCC option). Cannot be combined with DTR. (4) DTR - cannot be combined with BLD. (5) ECW - cannot be combined with BBJ, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC. (8) OCC - integral microwave motion sensor (ON/OFF). (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with ES. (10) PCH/PC4 - cannot be combined with BLD or OCC. Add'l Notes: \*BBI/BBC - BBI minimum operating temp: 10C/50F unless otherwise stated. BBC minimum operating temp: 20C/-4F. \*\*BLD - integral microwave motion sensor with step-dim control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to set level. 3: Remain in continuous dimmed state or turn off after set period. Configurable via onboard dip switches. Specifications and dimensions subject to change without notice.

