

# HANOVER [SWIRL]

**\*WILL BE DISCONTINUED SOON**  
CONTACT FACTORY FOR AVAILABILITY

PROJECT:
MODEL #:
FIXTURE TYPE:

## STANDARD SPECIFICATIONS

### PAN

The classic decorative layered look in a 20 GA cold rolled steel spinning.

### DIFFUSER

Formed glass, with a faux alabaster finish and an etched outer surface that softens the light. The diffuser is held in place by a cold rolled steel check ring, and a solid brass ball finial.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs  
Amperage rated @ 110V input  
Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B12 - 12W nominal, .10 A input - 1255 lm. Dimmable (0-10V).

C17 - 16W nominal, .15 A input - 1813 lm. Dimmable (0-10V).

C24 - 23W nominal, .20 A input - 2487 lm. Dimmable (0-10V).

### MOUNTING

Directly to j-box (by others). Mounting hardware included.

### FINISH

The 2126 series is finished in either electroplated brush nickel or high reflectance white powder coat. Also available in all Brownlee paint finishes. Plated finishes such as Brushed Nickel are suitable for indoor applications only. Installation outdoors voids the Brownlee Limited Warranty.

### WARRANTY


5 year limited warranty on this LED product. Consult factory for details.



BN finish



BZ finish



**DAMP**



## ORDERING INFORMATION

**2126** - Model - 2. - 3. - 4. - 5. - 6. (if required)

2. SIZE	3. FINISH	4. WATTAGE	5. COLOR TEMPERATURE	6. AVAILABLE OPTIONS
13 13" dia.	<b>STANDARD</b>	<b>13 SIZE</b>	<b>35K</b> 3500K standard color temperature	<b>90R<sup>0</sup></b> 90 CRI (3000K only)
15 15" dia.	<b>BN</b> Brushed Nickel	<b>B12</b> 12W B Series LED	<b>27K</b> 2700K color temperature	<b>BAC<sup>1</sup></b> Buy American Compliant
	<b>OPTIONAL</b>	<b>15 SIZE</b>	<b>30K</b> 3000K color temperature	<b>BBI<sup>2*</sup></b> Integral Battery Backup (8W) (15 size only) <i>Battery must be connected to continuous power supply within 7 Mo. of shipping. See Warranty Note 3.</i>
	<b>BL</b> Black	<b>B12</b> 12W B Series LED	<b>40K</b> 4000K color temperature	<b>BLD<sup>3**</sup></b> Bi-Level Dimming (15 size only)
	<b>BZ</b> Bronze	<b>C17</b> 16W C Series LED		<b>DTR<sup>4</sup></b> Triac (Line Voltage) Dimming (120V)
	<b>GM</b> Gun Metal	<b>C24</b> 23W C Series LED		<b>ES<sup>6</sup></b> ENERGY STAR® (Not available in 90 CRI)
	<b>MB</b> Metallic Bronze			<b>FCL<sup>7</sup></b> French Canadian Labels
	<b>MG</b> Metallic Gold			<b>OCC<sup>8</sup></b> Occupancy Sensor (15 size only)
	<b>NT</b> Nickel Tone			<b>T24<sup>9</sup></b> Title 24 JA8 Compliant (B12 & C24 in 3000K only)
	<b>PL</b> Platinum			
	<b>WH</b> White			
	<b>CUSTOM</b>			
	Provide color sample or RAL code to match			

**Universal Footnotes (only applies if option is listed on spec sheet):** (0) 90R - 90 CRI output-loss multiplier: 0.85 (estimate). Cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW or EXT. (3) BLD - includes integral microwave motion sensor (do not combine with OCC option). Cannot be combined with DTR. (4) DTR - cannot be combined with BLD. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC. (8) OCC - integral microwave motion sensor (ON/OFF). (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with ES. (10) PCH/PC4 - cannot be combined with BLD or OCC. **Add'l Notes:** \*BBI/BBC - BBI minimum operating temp: 10C/50F unless otherwise stated. BBC minimum operating temp: -20C/-4F. \*\*BLD - integral microwave motion sensor with step-dim control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to set level. 3: Remain in continuous dimmed state or turn off after set period. Configurable via onboard dip switches.

### Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.