




White Linen (WHL) diffuser

**2323 LED**

The 2323 is a decorative yet functional semi-flush mount with the several fabric options to choose from. Peruse our fabric offering in the resources section of the website for a variety of coordinated fabric pendants and sconces.

**TRIM FINISHES**



# FABO

## STANDARD SPECIFICATIONS

### TRIM

Cold rolled steel, formed in a die, finished with an electroplated brushed nickel coating that will withstand most nicks and scratches.

### DIFFUSER

Translucent, UV stabilized white acrylic. The drum shape features a fabric material bonded to the walls, allowing for ease of cleaning with a dry or damp cloth. You can choose from a selection of fabrics.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs

Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B12 - 12W nominal, .10 A input - 1547 lm. Dimmable (0-10V).

C17 - 16W nominal, .15 A input - 2235 lm. Dimmable (0-10V).

C24 - 23W nominal, .20 A input - 3066 lm. Dimmable (0-10V).

### MOUNTING

The 2323 is designed to be mounted directly to a j-box (by others). Mounting hardware included.

### FINISH

The standard finish is a sturdy electroplated brushed nickel. Options include all Brownlee paint finishes. Plated finishes such as Brushed Nickel are suitable for indoor applications only. Installation outdoors voids the Brownlee Limited Warranty.

### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

## ORDERING INFORMATION

**2323** - \_\_\_\_\_  
 Model                      2.                      3.                      4.                      5.                      6. (if required)

### 2. FINISH

**STANDARD**  
**BN**      Brushed Nickel

**OPTIONAL**  
**BL**      Black  
**BZ**      Bronze  
**GM**      Gun Metal  
**MB**      Metallic Bronze  
**MG**      Metallic Gold  
**NT**      Nickel Tone  
**PL**      Platinum  
**WH**      White

**CUSTOM**  
 Provide color sample or  
 RAL code to match

### 3. WATTAGE

**B12**      12W B Series LED  
**C17**      16W C Series LED  
**C24**      23W C Series LED

### 4. DIFFUSER

**WHA** White Acrylic  
**GYL** Grey Linen  
**NAL** Natural Linen  
**WBK** Woven Black  
**WHL** White Linen

Note: MAL & ROW - have been discontinued on this model - contact factory for availability.

### 5. COLOR TEMPERATURE

**35K**      3500K standard color temperature  
**27K**      2700K color temperature  
**30K**      3000K color temperature  
**40K**      4000K color temperature


### 6. AVAILABLE OPTIONS

**90R<sup>0</sup>**      90 CRI (3000K only)  
**BAC<sup>1</sup>**      Buy American Compliant  
**BLD<sup>3\*\*</sup>**      Bi-Level Dimming  
**DTR<sup>4</sup>**      Triac (Line Voltage) Dimming (120V)  
**ES<sup>6</sup>**      ENERGY STAR® (Not available in 90 CRI)  
**FCL<sup>7</sup>**      French Canadian Labels  
**OCC<sup>8</sup>**      Occupancy Sensor  
**T24<sup>9</sup>**      Title 24 JA8 Compliant (B12 & C24 in 3000K only)

<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>



BN finish, WHL diffuser



**DAMP**



**Universal Footnotes (only applies if option is listed on spec sheet):** (0) 90R - 90 CRI output-loss multiplier: 0.85 (estimate). Cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW or EXT. (3) BLD - includes integral microwave motion sensor (do not combine with OCC option). Cannot be combined with DTR. (4) DTR - cannot be combined with BLD. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC. (8) OCC - integral microwave motion sensor (ON/OFF). (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with ES. (10) PCH/PC4 - cannot be combined with BLD or OCC. **Add'l Notes:** \*BBI/BBC - BBI minimum operating temp: 10C/50F unless otherwise stated. BBC minimum operating temp: -20C/-4F. \*\*BLD - integral microwave motion sensor with step-dim control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to set level. 3: Remain in continuous dimmed state or turn off after set period. Configurable via onboard dip switches.

### Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.