



Grey Linen (GYL) diffuser



Grey Linen (GYL) diffuser

## 2662 LED

The 2662 LED features a one-piece tapered drum which is offered in three different sizes and two acrylic-backed fabric options. The base (bottom) of the drum is constructed of high transmission matte-white acrylic, providing optimal light distribution and performance. Two suspension options to choose from with extension kits available for high ceilings and staggered drops. The top of the drum is fully covered by the LED assembly to minimize debris entry. Given the size range, this unit is ideal for commercial lobbies and common areas, open-office layouts, conference rooms, break rooms, and

### FINISHES



# TAPER

## STANDARD SPECIFICATIONS

### DIFFUSER

The drum features a high quality UV stabilized white acrylic outer shell, with your choice of fabric bonded to its exterior sidewall. The base (bottom) of the drum is constructed with high transmission white acrylic. The fixture can be cleaned with a damp cloth and mild detergent, if needed.

### HOUSING

Formed, cold rolled steel design, finished in a high reflectance powder coat white. The housing covers the entire top surface of the drum. No need for top cover.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs  
Amperage rated @ 110V input  
Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K CCT noted. Consult Brownlee.com for performance of all CCTs.

B12 - 12W nominal, .10 A input - 1509 lm. Dimmable (0-10V).  
C17 - 16W nominal, .15 A input - 2297 lm. Dimmable (0-10V).  
C24 - 23W nominal, .20 A input - 3152 lm. Dimmable (0-10V).  
C37 - 35W nominal, .30 A input - 4414 lm. Dimmable (0-10V).  
C49 - 45W nominal, .40 A input - 5948 lm. Dimmable (0-10V).

### SUSPENSION SYSTEM

The 2662 Series is available in multiple colors and two suspension methods:

**CC1 - Cord & Single Cable:** Both the power cord and aircraft cable can be trimmed in the field. See optional ordering code CE1 and CE2 for extended 10' and 20' drops.

**SSM - Single Stem Mount:** Traditional pendant style. Steel stem in your choice of finish. The standard overall height (OAH) can be extended with additional stem sections in 1' and 2' intervals - see accessories section.

### MOUNTING

Directly to j-box (by others). Mounting hardware included.

### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

### ORDERING INFORMATION

2662	Model	2.	3.	4.	5.	6.	7.	8. (if required)
<b>2. SIZE</b>		<b>4. WATTAGE</b>		<b>5. DIFFUSER</b>		<b>7. COLOR TEMPERATURE</b>		
12 12" dia.		<b>12 SIZE</b>		<b>GYL</b> Grey Linen		<b>35K</b> 3500K standard color temperature		
16 16" dia.		<b>B12</b> 12W B Series LED		<b>WHL</b> White Linen		<b>27K</b> 2700K color temperature		
22 22" dia.		<b>16 SIZE</b>				<b>30K</b> 3000K color temperature		
		<b>B12</b> 12W B Series LED		<b>6. SUSPENSION</b>		<b>40K</b> 4000K color temperature		
<b>3. FINISH</b>		<b>C17</b> 16W C Series LED		<b>CC1</b> Cord & Single Cable		<b>8. AVAILABLE OPTIONS</b>		
<b>CC1</b>		<b>C24</b> 23W C Series LED		<b>SSM</b> Single Stem Mount		<b>90R<sup>0</sup></b> 90 CRI (3000K only)		
<b>BL</b> Black		<b>22 SIZE</b>				<b>BAC<sup>1</sup></b> Buy American Compliant		
<b>NT</b> Nickel Tone		<b>C37</b> 35W C Series LED				<b>CE1</b> 3' - 10' Cord/Cable Extension (CC1 only)		
<b>WH</b> White		<b>C49</b> 45W C Series LED				<b>CE2</b> 10' - 20' Cord/Cable Extension (CC1 only)		
						<b>DTR<sup>4</sup></b> Triac (Line Voltage) Dimming (120V)		
<b>SSM</b>						<b>ES<sup>6</sup></b> ENERGY STAR® (Not available in 90 CRI)		
<b>BL</b> Black						<b>FCL<sup>7</sup></b> French Canadian Labels		
<b>BZ</b> Bronze						<b>SVL</b> Swivel Canopy (SSM only)		
<b>GM</b> Gun Metal						<b>T24<sup>9</sup></b> Title 24 JA8 Compliant (B12, C24 & C49 in 3000K only)		
<b>MB</b> Metallic Bronze								
<b>MG</b> Metallic Gold								
<b>NT</b> Nickel Tone								
<b>PL</b> Platinum								
<b>WH</b> White								

**ACCESSORIES** (field installed - order separately)  
**390002xx** SSM Extension Kit: includes (1) 1' stem and (2) 2' stems. 5' combined max. Specify finish (xx)

**Notes:** (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW or EXT.  
 (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR. (4) DTR - cannot be combined with BLD or T24.  
 (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC.  
 (8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with DTR or ES.  
 (10) BBS - cannot be combined with BLD, ECW, EXT, or OCC. (11) PCH/PC4 - cannot be combined with BLD or OCC.  
**Add'l Notes:** \*BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\*BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50%, 30%, 20% or 10%. 3: Remain in continuous dimmed state or turn off after set period.

**Specifications and dimensions subject to change without notice.**  
 Consult your Brownlee Lighting representative for availability and ordering information.

<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>

