

CLOUD [LINEAR]

STANDARD SPECIFICATIONS

HOUSING

Cold rolled steel, die-formed, welded assembly. The housing can be mounted horizontal or vertical.

DIFFUSER

UV stabilized white acrylic. Diffuser is molded in the classic puff design. The material can withstand minor impact without breaking.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 90+ CRI - L80 rating (projected) - 60,000 hrs - L70 rating (projected) - 100,000 hrs
 Delivered lumens noted. Amperage rated @ 110V input
 Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

H16 - 16W nominal, .14 A input - 1657 lm. Dimmable (0-10V).
 H25 - 25W nominal, .20 A input - 2446 lm. Dimmable (0-10V).
 H32 - 32W nominal, .26 A input - 3280 lm. Dimmable (0-10V).


MOUNTING

Fixture uses wall anchors (by others) appropriate for the mounting surface.

WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

PROJECT:
MODEL #:
FIXTURE TYPE:



DAMP



ORDERING INFORMATION

5057	2.	3.	4.	5. (if required)
Model				
	2. SIZE	3. WATTAGE	4. COLOR TEMPERATURE	
	27 L: 27"	27 SIZE	35K 3500K standard color temperature	
	39 L: 39"	H16 16W H Series LED	30K 3000K color temperature	
	51 L: 51"	39 SIZE	40K 4000K color temperature	
		H25 25W H Series LED		
		51 SIZE		
		H32 32W H Series LED		
			5. AVAILABLE OPTIONS	
			BAC ¹ Buy American Compliant	
			BBI ^{2*} Integral Battery Backup (8W) (H25 & H32 only) Battery must be connected to continuous power supply within 7 Mo. of shipping. See Warranty Note 3.	
			DTR ⁴ Triac (Line Voltage) Dimming (120V)	
			ES ⁶ ENERGY STAR® (Not available in 90 CRI)	
			FCL ⁷ French Canadian Labels	
			T24 ⁹ Title 24 JA8 Compliant	

Universal Footnotes (only applies if option is listed on spec sheet): (0) 90R - 90 CRI output-loss multiplier: 0.85 (estimate). Cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW or EXT. (3) BLD - includes integral microwave motion sensor (do not combine with OCC option). Cannot be combined with DTR. (4) DTR - cannot be combined with BLD. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC. (8) OCC - integral microwave motion sensor (ON/OFF). (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with ES. (10) PCH/PC4 - cannot be combined with BLD or OCC. **Add'l Notes:** *BBI/BBC - BBI minimum operating temp: 10C/50F unless otherwise stated. BBC minimum operating temp: -20C/-4F. **BLD - integral microwave motion sensor with step-dim control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to set level. 3: Remain in continuous dimmed state or turn off after set period. Configurable via onboard dip switches. **Specifications and dimensions subject to change without notice.**
 Consult your Brownlee Lighting representative for availability and ordering information.