

HAVANA

STANDARD SPECIFICATIONS

HOUSING + FRAME

Formed aluminum construction, stainless steel fasteners.

DIFFUSER

UV stabilized white acrylic, formed into a "U" shape and held in position with construction tabs welded inside the housing.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
 Amperage rated @ 110V input
 Operating ambient temperature: -20°C / -4°F - 50°C / 122°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B06 - 6W nominal, .05 A input - 340 lm. Non-dimming.
 B12 - 12W nominal, .10 A input - 671 lm. Dimmable (0-10V).
 C09 - 9W nominal, .10 A input - 473 lm. Dimmable (0-10V).
 C17 - 16W nominal, .15 A input - 970 lm. Dimmable (0-10V).
 C24 - 23W nominal, .20 A input - 1331 lm. Dimmable (0-10V).

MOUNTING

Directly to j-box (by others). Mounting hardware included.

FINISH

The 7326 series is available in most Brownlee powder coat finishes as a standard offering.


WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

PROJECT:
MODEL #:
FIXTURE TYPE:



BL finish



WET



ORDERING INFORMATION

7326

Model 2. 3. 4. 5. (if required)

2. FINISH

STANDARD

AB	Antique Bronze
AS	Antique Silver
BL	Black
BZ	Bronze
DB	Desert Bronze
GM	Gun Metal
MB	Metallic Bronze
NT	Nickel Tone
PL	Platinum
WH	White

CUSTOM

Provide color sample or RAL code to match

3. WATTAGE

B06	6W B Series LED
B12	12W B Series LED
C09	9W C Series LED
C17	16W C Series LED
C24	23W C Series LED

4. COLOR TEMPERATURE

35K	3500K standard color temperature
27K	2700K color temperature
30K	3000K color temperature
40K	4000K color temperature

5. AVAILABLE OPTIONS

BAC¹	Buy American Compliant
DTR⁴	Triac (Line Voltage) Dimming (120V) (All except B06)
ECW⁵	Extreme Cold Weather (-40°C / -40°F min.)
ES⁶	ENERGY STAR®
FCL⁷	French Canadian Labels
OCC⁸	Occupancy Sensor
T24⁹	Title 24 JA8 Compliant (B12 & C24 in 3000K only)

Notes: (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW, EXT, or T24. (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) DTR - cannot be combined with BLD or T24. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC or T24. (8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI, BBC, BBS, BLD, DTR, ES, or FCL. (10) BBS - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) PCH/PC4 - cannot be combined with BLD or OCC.
Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. **BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.

