

Nickel Tone (NT) trim finish



VB0 trim

VB1 trim

VB2 trim

### 7601 LED

The 7600 series (Models: 7600/01/02/04/10/12/14/16) is available in a variety of sizes and lumen packages, making it highly versatile for exterior facades. Constructed of aluminum with your choice of durable powder coat finish, sturdy acrylic diffuser, and stainless steel hardware. Use this architectural sconce for any application requiring performance and a decorative aesthetic. Perfect for exterior facades, columns, breezeways, pool decks, and more. Vertical bars optional. Integral battery backup and cold weather integral battery backup optional.

### FINISHES



# PRO-15 [H4]

## STANDARD SPECIFICATIONS

### FRAME

Heavy duty aluminum with roll formed aluminum bands. The optional trim bars are solid 0.250" thick aluminum, held in place by fasteners.

### DIFFUSER

Translucent, UV stabilized, white acrylic. Diffuser is form molded allowing for a uniform standard thickness of 0.100" throughout.

### PAN

Heavy duty formed aluminum, featuring thread inserts to prevent rusting of fasteners.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs  
 Amperage rated @ 110V input  
 Operating ambient temperature: -20°C / -4°F - 50°C / 122°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

- B06 - 6W nominal, .05 A input - 484 lm. Non-dimming.
- B12 - 12W nominal, .10 A input - 957 lm. Dimmable (0-10V).
- C09 - 9W nominal, .10 A input - 675 lm. Dimmable (0-10V).
- C17 - 16W nominal, .15 A input - 1594 lm. Dimmable (0-10V).
- C24 - 23W nominal, .20 A input - 2186 lm. Dimmable (0-10V).

### MOUNTING

Directly to j-box (by others). Mounting hardware included.

### FINISH

All 7601 parts are prepared using a three step pre-treatment/sealing process, followed by a powder coat primer prior to applying any of the Brownlee paint finishes.

### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

## ORDERING INFORMATION

**7601** - \_\_\_\_\_  
 Model                      2.                      3.                      4.                      5.                      6. (if required)

### 2. FINISH

#### STANDARD

- AB** Antique Bronze
- AS** Antique Silver
- BL** Black
- BZ** Bronze
- DB** Desert Bronze
- GM** Gun Metal
- MB** Metallic Bronze
- NT** Nickel Tone
- PL** Platinum
- WH** White

#### CUSTOM

Provide color sample or RAL code to match

### 3. WATTAGE

- B06** 6W B Series LED
- B12** 12W B Series LED
- C09** 9W C Series LED
- C17** 16W C Series LED
- C24** 23W C Series LED

### 4. TRIM

- VB0** No trim
- VB1** 1 vertical bar\*
- VB2** 2 vertical bars\*

\*Does not meet ADA requirements

### 5. COLOR TEMPERATURE

- 35K** 3500K standard color temperature
- 27K** 2700K color temperature
- 30K** 3000K color temperature
- 40K** 4000K color temperature


### 6. AVAILABLE OPTIONS

- BAC**<sup>1</sup> Buy American Compliant
- BBI**<sup>2\*</sup> Integral Battery Backup (8W) (adds 1.5" to depth)
- BBC**<sup>2\*</sup> Integral Battery Backup, Cold Weather (16W) (adds 1.5" to depth)  
Battery must be connected to continuous power supply within 7 Mo. of shipping. See Warranty Note 3.
- BLD**<sup>3\*\*</sup> Bi-Level Dimming (All except B06)
- DTR**<sup>4</sup> Triac (Line Voltage) Dimming (120V) (All except B06)
- ECW**<sup>5</sup> Extreme Cold Weather (-40°C / -40°F min.)
- ES**<sup>6</sup> ENERGY STAR®
- EXT** Extended Housing (Intended to match BBI(C) aesthetic) (Adds 1.5" to depth)
- FCL**<sup>7</sup> French Canadian Labels
- OCC**<sup>8</sup> Occupancy Sensor
- T24**<sup>9</sup> Title 24 JA8 Compliant (B12 & C24 in 3000K only)

<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>



NT finish, VB0 trim



\*Note: For a proportionally larger size, refer to Model #: 7600 LED.



WET



**Universal Footnotes (only applies if option is listed on spec sheet):** (0) 90R - 90 CRI output-loss multiplier: 0.85 (estimate). Cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW or EXT. (3) BLD - includes integral microwave motion sensor (do not combine with OCC option). Cannot be combined with DTR. (4) DTR - cannot be combined with BLD. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC. (8) OCC - integral microwave motion sensor (ON/OFF). (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with ES. (10) PCH/PC4 - cannot be combined with BLD or OCC. **Add'l Notes:** \*BBI/BBC - BBI minimum operating temp: 10C/50F unless otherwise stated. BBC minimum operating temp: -20C/-4F. \*\*BLD - integral microwave motion sensor with step-dim control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to set level. 3: Remain in continuous dimmed state or turn off after set period. Configurable via onboard dip switches. **Specifications and dimensions subject to change without notice.**

Consult your Brownlee Lighting representative for availability and ordering information.