



Nickel Tone (NT) trim finish

7610 LED

The 7600 series (Models: 7600/01/02/04/10/12/14/16) is available in a variety of sizes and lumen packages, making it highly versatile for exterior facades. Constructed of aluminum with your choice of durable powder coat finish, sturdy acrylic diffuser, and stainless steel hardware. Use this architectural sconce for any application requiring performance and a decorative aesthetic. Perfect for exterior facades, columns, breezeways, pool decks, and more. Vertical bars optional. Integral battery backup and cold weather integral battery backup optional.

FINISHES



PRO-41 [HS]

STANDARD SPECIFICATIONS

FRAME

Heavy duty aluminum with roll formed aluminum bands. The trim bars are solid 0.250" thick aluminum, held in place by fasteners.

DIFFUSER

Translucent, UV stabilized, white acrylic. Diffuser is form molded allowing for a uniform standard thickness of 0.100" throughout.

PAN

Heavy duty formed aluminum, featuring aluminum thread inserts to prevent rusting of fasteners.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 90+ CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
 Amperage rated @ 110V input
 Dimming compatible - 0-10V control required
 Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

H32 - 32W nominal, .26 A input - 1636 lm. Dimmable (0-10V).
 H41 - 41W nominal, .35 A input - 1998 lm. Dimmable (0-10V).

MOUNTING

The 7610 series is designed to be mounted directly to the wall with (4) 1/4" anchors (not included).

FINISH

All 7610 parts are prepared using a three step pre-treatment/sealing process, followed by a powder coat primer prior to applying any of the Brownlee paint finishes.


WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

PROJECT:
MODEL #:
FIXTURE TYPE:



NT finish



ORDERING INFORMATION

7610 - _____ - _____ - _____ - _____ - _____
 Model 2. 3. 4. 5. (if required)

2. FINISH

STANDARD

- AB** Antique Bronze
- AS** Antique Silver
- BL** Black
- BZ** Bronze
- DB** Desert Bronze
- GM** Gun Metal
- MB** Metallic Bronze
- NT** Nickel Tone
- PL** Platinum
- WH** White

CUSTOM

Provide color sample or RAL code to match

3. WATTAGE

- H32** 32W H Series LED
- H41** 41W H Series LED

4. COLOR TEMPERATURE

- 35K** 3500K standard color temperature
- 30K** 3000K color temperature
- 40K** 4000K color temperature

5. AVAILABLE OPTIONS

- BAC**¹ Buy American Compliant
- BLD**^{3**} Bi-Level Dimming
- ES**⁶ ENERGY STAR® (H32 Only)
- OCC**⁸ Occupancy Sensor
- FCL**⁷ French Canadian Labels
- T24**⁹ Title 24 JA8 Compliant (H32 only)

Universal Footnotes (only applies if option is listed on spec sheet): (0) 90R - 90 CRI output-loss multiplier: 0.85 (estimate). Cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW or EXT. (3) BLD - includes integral microwave motion sensor (do not combine with OCC option). Cannot be combined with DTR. (4) DTR - cannot be combined with BLD. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC. (8) OCC - integral microwave motion sensor (ON/OFF). (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with ES. (10) PCH/PC4 - cannot be combined with BLD or OCC. **Add'l Notes:** *BBI/BBC - BBI minimum operating temp: 10C/50F unless otherwise stated. BBC minimum operating temp: -20C/-4F. **BLD - integral microwave motion sensor with step-dim control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to set level. 3: Remain in continuous dimmed state or turn off after set period. Configurable via onboard dip switches.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.

