STANDARD SPECIFICATIONS

HOUSING

Full cutoff design. Durable die-cast aluminum housing is composed of two parts with a hinged door for ease of maintenance, with a continuous gasket to prevent water intrusion. IP65 Rated.

Polycarbonate diffuser utilizes built-in optics to maximize light output and overall performance.

LED PERFORMANCE

120-277V - 4000K, 82 CRI - L70 rating - 76,000 hrs (projected) Operating ambient temperature: -20°C / -4°F - 40°C / 104°F Refer to Wattage section for lumen output.

MOUNTING

The 79005 is designed to be mounted directly to the surface and wired with rear conduit entry. Additional knockout ports are available for surface conduit entry on both sides and the top.

FINISH

This series is available in a standard bronze polyester powder coat. Select Brownlee paint finishes are also available as an option.

WARRANTY

5 year limited warranty on this LED product. Consult factory for details.








PROJECT: MODEL #: FIXTURE TYPE:





ORDERING INFORMATION

79005 Model

ΒZ

WH

SIZE

MD Medium

FINISH 3.

STANDARD

Bronze

OPTIONAL

BL Black GM Gun Metal NT Nickel Tone PL Platinum

White

CUSTOM

Provide color sample or RAL code to match

WATTAGE

P50LED 50W P Series LED, .52 A input,

5655 delivered lumens Replaces up to 175W MH*

*Based on lumainare lumen output

P80 wattage has been discontinued. Contact factory for limited availability. CCT

40K 4000K

FIELD INSTALLED ACCESSORIES (order separately)

ORDERING NUMBER	DESCRIPTION	NOTES
910037	Photocell (120-277V)	Universal voltage photocell. Field installed (by others).

P50LED 15' 30' 45' 60' 30' 15' 0' 5 2 1 .5 .2 15' Mounting Height: 15ft